

SOUTHAMPTON

Specification Sheet

ADA SAFETY EDGING

Application –
Construction –

Indoor and outdoor.
“Never-Fray” needlepunch construction eliminates the need for edging. Matting can be cut to any size or shape transitioning seamlessly from one to the next.

Texture –
Face Fiber –

Non-directional berber.
100% Solution dyed UV stabilized polypropylene for maximum stain and fade resistance.

Face Weight –

52 oz/sq yd is more than twice the weight of the average rental runner resulting in more water retention, durability, crush resistance, and aggressive soil removal.

Total Weight –
Total Height –
Backing –

.6 lb per square foot.
(3/8) inches (variable).
Modified rubber. Non yellowing and non staining. Easily rolls and unrolls flat while reducing mat “creeping” on hard floors. Velcro available for use on carpet.

Sizing –

Up to 13'-2" x 80' in a single piece enables us to manufacture any size or shape in the largest of lobbies.

Flammability –

Passed (DOC-FF-1-70) Pill test.

Water Retention –

(.8) gallons per square yard. Outperforms matting whose claim to fame is water retention.

3-Year Warranty –

100% in first year, 50% in second year, 25% in third year.

Installation –

Easy to self-install with a mat knife. Optional on site installation by a PROFORM certified master installer is available.

Storage Cores –

Optional Heavy Duty fiber storage cores insure that matting is ready to lay flat without curling. (Always store carpet side out.)

Edging Options –

Safety Edging: A 1.5" vinyl reducer which is applied with glue and stitched, with mitered corners and reinforced with vinyl corner supports.

Cleaning –

Regular vacuuming, carpet extraction or bonnet cleaning as needed.

LEED: Possible LEED-NC credits: MR Credit 4 (1-2 points), IEQ Credit 4.1 (1 point)
Recycled Content: 15% post-consumer



Because you never get a second chance to make a first impression.

888.331.3100 • www.proformmat.com